

# IP-CS3068

## IP POE CEILING SPEAKER

### Product Features

- ❑ Fully digital transmission with POE power supply mode, high fidelity CD-level sound quality,
- ❑ Built-in 8GByte SSD, support server remote management, limited bandwidth background download or automatic download at idle time, which can reduce network burdens. Offline automatic play function can be used in media library file.
- ❑ Max connection distance: 100 meters.
- ❑ Equipped with DC 24V standby power interface, suitable for power supply when power demand is greater than 10W or for non-POE network.



### Technical Specifications

Rated Power	8W
Network Interface	Standard RJ45 input with 100Mbps
Supporting Protocols	TCP/IP, UDP, IGMP (Multicast), SIP, VoIP, VOIP
Sampling Rate / Bit Rate	8k ~ 48kHz / 8kbps ~ 512kbps
Audio Format & Mode	MP3; 16-bit CD sound quality
Total / Standby Power Consumption	12W / < 3W
Frequency Response	80 ~ 16kHz 3dB ± 1dB
THD	≤ 1%
SNR	≥ 68 dB
Loaded Speaker	8Ω / 6W
Speaker Attribute	Woofer
Protection Circuit	Overvoltage, overcurrent protection
Working Voltage	190V ~ 240V AC with 50Hz ~ 60Hz; DC 24V/1.5A
Working Temperature / Humidity	5°C ~ 40°C; 20% - 80% Relative humidity, without condensation
Installation Size	160 mm
Size (D x H)	180 x 98 mm
Weight	0.8kg