

Product Features

- ❑ Full touch screen control as it comes with 8-inch capacitive touch screen.
- ❑ Real-time display of status information such as Program broadcast, two-way intercom, timed broadcast, equipment operation, IP address, MAC address, and other; a button is supported to stop the program broadcast.
- ❑ Graphical volume adjustment interface to adjust the volume of network programs, local MIC, and local AUX.
- ❑ Support for voice reporting, lighting, text, and other prompts, one-key answering, one-key monitoring, hands-free calls, and the function to record missed call details.
- ❑ 2 short-circuit outputs, 2 short-circuit inputs; support flexible short-circuit triggering customized task function.

IP-PMC3100

IP PAGING MICROPHONE



Technical Specifications

Network Interface	Standard RJ45 Input with 1000Mbps / 100Mbps
Communication Protocol	TCP/IP, UDP, IGMP (Multicast), IETF SIP
Sampling Rate	8k ~ 48kHz
AUX Input & Sensitivity	1 Group (350mV)
MIC Input & Sensitivity	1 Group (10mV)
Line Output Level / Impedance	1 Group (1000mV / 470 Ω)
Microphone Type	Cardioid directional electret
Headphone Output Interface & Load	3.5mm interface & 32 Ω
Power Consumption (Total / Standby)	20W / < 3W
Frequency Response	80Hz ~ 16kHz -3dB ± 1dB
THD	≤ 1%
SNR	> 65dB
Short Circuit	Support dry contact; Input: 0V/3.3V; Output: Max 1A/30VDC
Working Voltage	190V ~ 240V AC with 50Hz ~ 60Hz; DC 24V/1.5A
Working Temperature / Humidity	5°C ~ 40°C
Size (L x D x H)	200 x 159 x 55 mm
Weight	1.05kg