

Product Features

- ❑ IP power amplifier that with output power 120W / 240W / 350W / 500W
- ❑ Comes with 4.3-inch LCD screen in TFT colour, 21 industrial metal buttons, graphical volume adjustment interface for the volume of network programs, local MICs and local AUX.
- ❑ Real-time display of status information such as program broadcast, timed broadcast, equipment operation, IP address, MAC address, and so on; support stopping the program broadcast with one button.
- ❑ Smart power management function: automatically cut off the power of the amplifier when no signal, and automatically start the programmed pre-power on function when entering the standby mode and the power is less than 10W.

IP-AMP120/ 240/350/500

IP POWER AMPLIFIER



Technical Specifications

Model	T-78120	T-78240	T-78350	T-78500
Rated Power Output	120W	240W	350W	500W
Total / Standby Power Consumption	160W / < 10W	320W / < 10W	460W / < 10W	650W / < 10W
Network Interface & Transmission Rate	Standard RJ45 Input with 100Mbps			
Protocol	TCP/IP, UDP, IGMP (Multicast), IETF SIP			
Sampling Rate	8k ~ 48kHz			
AUX Input & Sensitivity	1 Group (350mV)			
EMC Input & Sensitivity	1 Group (775mV)			
MIC Input & Sensitivity	1 Group optional TRS interface or 3.5mm input (5mV / 10mV)			
Line Output Level / Impedance	1 Group with 1000mV / 470 Ω			
Earphone Connector / Load	3.5mm interface / 32 Ω			
USB / SD	MAX 4T USB device / MAX 128G SDXC card			
Frequency Response	80Hz ~ 16kHz -3dB ± 1dB			
THD	≤ 1%			
SNR	> 65 dB			
Short Circuit	Support dry contact; Input: 0V/3.3V; Output: Max 1A/30VDC			
Protection Circuit	DC output, overload, over temperature, short circuit protection			
Working Temperature & Humidity	5°C ~ 40°C; 20% - 80% Relative humidity, without condensation			
Working Voltage	190V ~ 240V AC with 50Hz ~ 60Hz			
Size	484 x 327 x 88 mm			
Weight	9.6 kg	9.6 kg	16.5 kg	18 kg