HS-5002/ 3003

REFLEX HORN SPEAKER

Build with IP 56 standard, the HS-5002 (50W) and HS-3003 (30W) is a weather resistant horn speaker that can be use indoor and outdoor sound system. It is well suited for voice paging, background music and tone signalling distribution due to its wide frequency range. The HS-5002/3003 has a 108dB SPL, suitable for big premises. Each unit comes with a waterproof PG-screw joint that acts as a seal to protect the sensitive components from the threats of the environment. The speakers equipped with 2 pole connection cable of known as flexible hose line that links to the PG-screw joint and also comes with switchable 6-step impedance located at the rear side of the unit.

Technical Specifications

Model	HS-5002	HS-3003
Rated Power	50W	30W
Input Impedance	100/200/330/670/16Ω	166/330/500/1k/16Ω
Frequency Response	350Hz - 5kHz	350Hz – 5kHz
SPL (1W, 1M) dB	108dB	108dB
Output Power	50/25/15/7.5W (70V) 50/30/15W (100V)	30/15/10/5W (70V) 30/20/10W (100V)
Dimension (DxH)	⌀ 500 x 463 mm	⌀ 500 x 463 mm
IP Rating	IP 56	IP 56

Physical

Horn Material	Aluminium	Aluminium
Cover Material	ABS	ABS